BAR LINE

ICE . MACHINES

Also available in the self-contained range for "Bistrot" cube: B 1706, B 3515, B 4422, B 5522, B 7040, B 8040, B 9050 See pertaining literature for more details







B 2608 AS/WS

Bar-Line Equipment range is the newly released EU made ice makers for Thimble-shaped rounded ice cubes coming from Bar-Line.

Built in the Italian manufacturing plant of Frimont Spa, ISO 9001 Certified, these units are built with sturdy, corrosion resistant stainless steel, and feature European made componentry to assure maximum quality and reliability. Tested one by one, the Bar-Line self contained units feature well balanced ratio between production and storage capacity, alongside with reduced outer dimensions that allow for built-in installations.

Front air louvers assure appropriate airflow in critical install requirements. Contemporary, elegant design unites excellent operational features with the reliability obtained through years of successful experience in ice making technology.

Insulated bin door and ice storage bin minimize air condensation and water formation on equipment surfaces. Electromechanic controls maximise reliability and ease of repair during the entire life of the equipment.

2014 FUNCTIONALITY IMPROVEMENTS:

- Improved water distribution system alongside with evaporator assembly: a larger number of ice cubes is now produced per each cycle, while the newly designed water distribution spray system provides best evaporator surface coverage and is simple to remove during routine cleaning.
- Optimized dimensions and production/ storage ratios. Easier to fit even under lowest bar counters and in reduced footprint spaces.
- Front panel installed thermostatic controls for ice cube size and storage bin ice level sensor. Easily accessible, allow for an easy adjustment of the key working parameters of the machine.
- Bin door slide rollers for a smooth openclose movement, with door movement rubber, sound dampening, shock absorbers.
- Utilities connection may run through side panel openings, for a reduced depth installation requirement.


515 mm

for "Bistrot" cube: B 1706, B 3515,
B 4422, B 5522, B 7040, B 8040, B 9050
See pertaining literature for more details




B 2608 AS / WS 390 mm-638.5 mm 640 mm with legs Air out Air in

> 515 mm (20 1/4") 540 mm (25 3/16") 638.5 mm 25 1/8



mm



All specifications and performance data are subject to normal manufacturing variances.

All units have stainless steel finish.





	ر			
41 mm (1 5/8°)	S5 mm (2 3/16")	117 mm (4 5/8")	153 mm (6")	190 mm (7.1/2")
94 mm (3 11/16°) 3/4" GAS WATER INLE WATER COOLDED ON	Y Y	117 mm	153	190 mm
Ø20 mm WATER D	(3/16") RAIN GAS WA	ITER IN	B FT	
CORD SET				

ORDERING AND SPECIFICATION INFORMATION											
Model No	Cond. unit	ICE Production per 24 hrs, at 10°C Air/10°C Water Kg	ICE Production per 24 hrs. at 21°C Air/15°C Water Kg	Bin storage Kg	Voltage Characteristics	Refrigerant	Water Consumption Lt/h	Electric Consumption	Net Weight Kg	Max. Shipping Weight Kg	
B 2608 AS	Air	28	26	8,5	230/50/1	R404A	n.a.	n.a.	31	37	
B 2608 WS	Water	_ 28	26	8,5	230/50/1	R404A	n.a.	n.a.	31	37	

CE

We reserve the right to make changes in design and construction at any time without obligation. ADV-Bar-Line 9/2013



Frimont S.p.A.

Via Lainate 31/b - 20010 Pogliano Milanese - (Milano) Italy Tel. +39.02.93960.239 - Fax +39.02.93960.201 barline@frimont.it - www.barline.it