



G 18C

Beverages

Derby

Derby Product Line for Beverages

Developed to guarantee the success of your brand, the Derby Beverages Line combines performance and technology with the perfect exposure.

This line is composed by Upright, Horizontal and Impulse models with a cooler capacity between -9°C and 12°C, ideal for storage of juice, water, soft drinks, energy drinks and beverages in general.

Find out about Derby's design and technology and ensure your products always enjoy the perfect exposure at the point of sale.

Derby: tradition of innovation, always offering the best design in quality, finishing, and performance.



Adjustable feet

Adjustable shelves

Make the arrangement and identification of the products easy.

• Branding*

Custom graphics can also be added.

• Built-in handle

Makes an easy opening of the door.

Door lock*

Avoids undesirable openings and secures the products inside.

Light canopy*

Helps spotlight your brand and adds attention at the point of sale.

Thermometer

Informs you about internal temperature.

* Options







ADJUSTABLE SHELVES

BUILT-IN HANDLE







THERMOMETER



BRANDING*

LOADING CAPACITY				
Can 3	30ml	182	Pet 500ml	60



DIMENSIONS



Gross (liters / cubic feet)	146 / 5.15
Net (liters / cubic feet)	136 / 4.80

External dimensions

Width (mm / inches)	595 / 23.42
Height (mm / inches)	865 / 34.05
Depth (mm / inches)	600 / 23.62

Internal dimensions

Width (mm / inches)	495 / 19.48
Height (mm / inches)	600 / 23.62
Depth (mm / inches)	500 / 19.68

Weight

Net (kg)		42

^{*} Not considered the compartment for the compressor.

TRANSPORTATION



47

D -			_ • -	
Pa	СК	aa	71 r	าต
	•		,	. 3

Width (mm / inches)	640 / 25.19
Height (mm / inches)	925 / 36.41
Depth (mm / inches)	700 / 27.55

Loading container

20 feet	-
40 feet	-

Piling up

Maximum


Weight

Gross (kg)



REAL SIZE





TEMPERATURE RANGE



Temperature range (°C)	1.9 to 9
Temperature range (°F)	35.42 to 48.2
Climate class	4

TECHNOLOGY



Type of evaporator	Plate
Type of refrigeration agent (gas)	R134A

POWER



Voltage / Frequency	230V - 50Hz
Voltage / Frequency	-
Voltage / Frequency	-
Power (W)	162
Energy consumption (KWh/24h)	-

MERCHANDISING AREA



Sidewall		Door	
Width (mm)	-	Width (mm)	-
Height (mm)	-	Height (mm)	-

OPTIONS



• Light Canopy • Door Lock





